



## Classic Sliding Pocket Door System – Single

Generated on 02.05.2017

### Detailed description

Sliding pocket doors are a space-saving alternative to a traditional hinged door for downstairs toilets, utility rooms, bathrooms, en-suites, storerooms and pantries, walk-in wardrobes ideal for any room where you wish to maximise the usable floor space in a property.

### Features:

- The door post, pocket and track assemble together and are inserted into the stud work as a complete unit which helps to ensure the door will run true and in line.
- Door slides into the pocket in the wall.
- Wide range of sizes to suit standard UK door sizes. Non-standard sizes on request up to 2 m wide and 3 m high door panel.
- Door panels up to 100 kg (150 kg on request).
- Suitable for use with 35 or 44 mm thick doors.
- Doors, plasterboard and final architrave not included.
- A wide range of glass pocket doors is available to suit the system – contact manufacturer for details.
- For fire-rated version see the Sliding Pocket Door - Single Fire-Rated specification.

### Advantages:

- Quick and easy to assemble and install.
- Complete with full wooden jamb kit for a professional finish.
- Maintenance-free track and runners.
- Fully extractable track, no need to break into the wall should you ever want to remove it.
- Fully adjustable front and rear doorstep.
- Self-centring floor guide with anti-warp profile.

### Options

#### Size:

The following frame sizes (in mm) are available:

- 1273 x 2056: To suit 610 x 1981 mm door. Clearance: 585 x 1971 mm.
- 1449 x 2056: To suit 686 x 1981 mm door. Clearance: 661 x 1971 mm.
- 1463 x 2056: To suit 711 x 1981 mm door. Clearance: 675 x 1971 mm.
- 1625 x 2056: To suit 762 x 1981 mm door. Clearance: 737 x 1971 mm.



#### Eclisse UK

Richmond House 2  
Occupation Lane  
Gonerby Moor  
Grantham  
Lincolnshire  
NG32 2BP

Tel: +44 (0)845 481 1977

[www.eclisse.co.uk](http://www.eclisse.co.uk)  
[info@eclisse.co.uk](mailto:info@eclisse.co.uk)



- 1701 x 2056: To suit 838 x 1981 mm door. Clearance: 813 x 1971 mm.
- 1888 x 2056: To suit 914 x 1981 mm door. Clearance: 900 x 1971 mm.
- 1663 x 2105: To suit 813 x 2032 mm door. Clearance 775 x 2020 mm.
- 1838 x 2105: To suit 864 x 2032 mm door. Clearance 850 x 2020 mm.
- 1288 x 2115: To suit 626 x 2040 mm door. Clearance: 600 x 2030 mm.
- 1488 x 2115: To suit 726 x 2040 mm door. Clearance: 700 x 2030 mm.
- 1688 x 2115: To suit 826 x 2040 mm door. Clearance: 800 x 2030 mm.
- 1888 x 2115: To suit 926 x 2040 mm door. Clearance: 900 x 2030 mm.
- 2088 x 2115: To suit 1026 x 2040 mm door. Clearance: 1000 x 2030 mm.

Bespoke sizes available on request.

#### Accessories:

- E-Motion Linear motor open/close. Can be operated by push button, infra red detector, remote control or radar sensor activator.
- Soft close: Slide the door towards the close position and the soft close takes over.
- Self closing mechanism: Open the door and it closes by itself.
- ECLISSE BIAS®: Soft Close anti-slam device with 40 kg soft closing.
- ECLISSE BIAS® DS: Bi-directional soft close up to 40 kg with anti-slam.

#### Product specification

##### Manufacturer

- Name: Eclisse UK
- Web: [www.eclisse.co.uk](http://www.eclisse.co.uk)
- Email: [info@eclisse.co.uk](mailto:info@eclisse.co.uk)
- Tel: +44 (0)845 481 1977
- Fax: +44 (0)1476 560710
- Address: Richmond House 2, Occupation Lane, Gonerby Moor, Grantham, Lincolnshire NG32 2BP

**Product reference** Classic Sliding Pocket Door System – Single

**Size** [ ]



<b>Finished wall thickness</b>	100 mm 125 mm
<b>Door furniture</b>	As schedule OSO8 - Polished brass simple flush pull. OSC4 - Antique brass simple flush pull. OSC2 - Polished chrome simple flush pull. OSC1 - Satin chrome simple flush pull. OSO3 - Polished brass bathroom lock. OSA - Antique brass bathroom lock. OSO1 - Polished chrome bathroom lock. OSS - Satin chrome bathroom lock.
<b>Accessories</b>	[Not required] [ECLISSE BIAS®] [ECLISSE BIAS® DS] [e-Motion motor] [Self closing mechanism] [Soft close]