



## Classic Sliding Pocket Door System – Single Fire-rated

Generated on 02.05.2017

### Detailed description

A sliding door system providing a larger passage width for standard UK approved 30 minute fire doors.

### Features:

Sliding pocket doors are a space-saving alternative to a traditional hinged door for downstairs toilets, utility rooms, bathrooms, en-suites, storerooms and pantries, walk-in wardrobes. Ideal for any room where you wish to maximise the usable floor space in a property.

- The door post, pocket and track assemble together and are inserted into the stud work as a complete unit which helps to ensure the door will run true and in line.
- Door slides into the pocket in the wall.
- Wide range of sizes to suit standard UK door sizes. Bespoke sizes available.
- Door panels up to 100 kg.
- Suitable for use with 44 mm FD30 fire doors.
- System comes with special jambs incorporating architraves.
- Doors not included.
- Use 15 x 4 mm intumescent strips and 12.5 mm plasterboard with a FD30 fire-rating (not supplied).

### Advantages:

- Quick and easy to assemble and install.
- Maintenance-free track and runners.
- Fully extractable track, no need to break into the wall should you ever want to remove it.
- Fully adjustable front and rear doorstop.
- Self-centring floor guide with anti-warp profile.

### Approvals:

The system was tested to BS EN 1634-1: 2008 for fire resistance at Cambridge Fire Research which is an independent UKAS accredited testing laboratory.

### Product guidance - As Standard

#### Finished wall thickness:

100 mm (for 125 mm contact manufacturer for details).

### Options

Eclisse UK



**Eclisse UK**  
Richmond House 2  
Occupation Lane  
Gonerby Moor  
Grantham  
Lincolnshire  
NG32 2BP

Tel: +44 (0)845 481 1977

[www.eclisse.co.uk](http://www.eclisse.co.uk)  
[info@eclisse.co.uk](mailto:info@eclisse.co.uk)



## Size:

Frames allow for maximum passage sizes as follows:

- 1273 x 2056: To suit 610 x 1981 mm door. Maximum passage size (w x h): 555 x 1951 mm.
- 1449 x 2056: To suit 686 x 1981 mm door. Maximum passage size (w x h): 631 x 1951 mm.
- 1625 x 2056: To suit 762 x 1981 mm door. Maximum passage size (w x h): 707 x 1951 mm.
- 1701 x 2056: To suit 838 x 1981 mm door. Maximum passage size (w x h): 783 x 1951 mm.
- 1888 x 2056: To suit 914 x 1981 mm door. Maximum passage size (w x h): 870 x 1951 mm.
- 1288 x 2115: To suit 626 x 2040 mm door. Maximum passage size (w x h): 570 x 2010 mm.
- 1488 x 2115: To suit 726 x 2040 mm door. Maximum passage size (w x h): 670 x 2010 mm.
- 1688 x 2115: To suit 826 x 2040 mm door. Maximum passage size (w x h): 770 x 2010 mm.
- 1888 x 2115: To suit 926 x 2040 mm door. Maximum passage size (w x h): 870 x 2010 mm.
- 2088 x 2115: To suit 1026 x 2040 mm door. Maximum passage size (w x h): 970 x 2010 mm.

Bespoke sizes available on request. Suitable for use with 44 mm FD30 doors only.

## Product specification

### Manufacturer

- Name: Eclisse UK
- Web: [www.eclisse.co.uk](http://www.eclisse.co.uk)
- Email: [info@eclisse.co.uk](mailto:info@eclisse.co.uk)
- Tel: +44 (0)845 481 1977
- Fax: +44 (0)1476 560710
- Address: Richmond House 2, Occupation Lane, Gonerby Moor, Grantham, Lincolnshire NG32 2BP

<b>Product reference</b>	Classic Sliding Pocket Door System – Single Fire-rated
<b>Size (mm)</b>	[ _____ ]
<b>Accessories</b>	[Not required] [Self closing mechanism]