



**N.B.:** Non standard sizes on request

FRAMES FOR SINGLE DOORS			DOOR PANEL UK	
MAX. PASSAGE SIZE PW x PH	OVERALL DIMENSION W x H	FINISHED WALL FW	DW	DH
600 x 2030	1301 x 2115	150	626	2040
700 x 2030	1501 x 2115	150	726	2040
800 x 2030	1701 x 2115	150	826	2040
900 x 2030	1901 x 2115	150	926	2040
1000 x 2030	2101 x 2115	150	1026	2040
585 x 1971	1286 x 2056	150	2ft. 0in. x 6ft. 6in. (610 x 1981 mm)	
661 x 1971	1462 x 2056	150	2ft. 3in. x 6ft. 6in. (686 x 1981 mm)	
737 x 1971	1638 x 2056	150	2ft. 6in. x 6ft. 6in. (762 x 1981 mm)	
813 x 1971	1714 x 2056	150	2ft. 9in. x 6ft. 6in. (838 x 1981 mm)	
900 x 1971	1901 x 2056	150	3ft. 0in. x 6ft. 6in. (914 x 1981 mm)	
675 x 1971	1476 x 2061	150	2ft. 4in. x 6ft. 6in. (711 x 1981 mm)	
775 x 2020	1676 x 2110	150	2ft. 8in. x 6ft. 8in. (813 x 2032 mm)	
850 x 2020	1851 x 2110	150	2ft. 10in. x 6ft. 8in. (864 x 2032 mm)	

Dimensions are given in mm



#### NOTES

- ▶ Available in non standard sizes up to 1300 x 2600 mm passage size.
- ▶ Standard single units have the possibility to use sockets on both sides of the pocket.
- ▶ Maximum socket depth 44 mm.
- ▶ Suitable for 35 to 44 mm thick doors.
- ▶ Max door weight 100 kg (150 kg on request).
- ▶ When fitting flush pull handles we recommend the stop be regulated so the door protrudes from the pocket to avoid risk to fingers.
- ▶ Should the door be adjusted to enter the pocket completely we do not accept any liability.
- ▶ The framework is not designed to take heavy loads such as radiators e.t.c..
- ▶ Doors, plasterboard and final architrave not supplied.
- ▶ Install at finished floor level.



#### ACCESSORIES

- ▶ **Door Furniture**  
Flush Pulls and Bathroom Locks
- ▶ **ECLISSE BIAS®**  
Safety Soft Close anti-slam device with 40 kg soft closing
- ▶ **ECLISSE BIAS® DS**  
Bi-directional Safety soft close up to 40 kg with anti-slam
- ▶ **Soft Close**  
Slide the door towards the close position and the soft close takes over.
- ▶ **Self Closing Mechanism**  
Open the door and it closes by itself!
- ▶ **E-MOTION**  
Linear motor open/close